



## Vehicle Mounted Terminals Slim, robust and powerful – VMT9000 series



NEW



Terminal VMT9000 series

**Industrial IT platforms for warehousing and logistics, as well as agricultural and construction machinery *Technology for professionals***

That's something you can count on. For more than three decades, ADS-TEC has continuously provided state of the art, powerful PC technology with an industrially-oriented design. Our complete depth of development and the state-of-the-art processes are the basis for customer-oriented products and individual solutions. Technology 100% made in Germany – a good feeling for ADS-TEC customers.



**VMT9000 series *Vehicle terminals of the fifth generation***

With its technologically advanced design and exceptional quality, the VMT9000 series is carrying on the tradition of award-winning ADS-TEC operating devices. The family of terminals and its wide range of features were developed specifically for the target markets of logistics and agricultural and construction machinery on the basis for almost 40 years of industry-specific experience. The VMT9000 series is characterised by an especially robust design to ensure reliable function even under the most demanding conditions.

With the VMT9000 series, you can select from freely configurable features based on the latest industrial-grade PC technology according to your company's individual needs.

# VMT9000 Series Product Benefits

## HIGHLIGHTS

- Can be used flexibly on forklifts and vehicles
- Compact design with high performance
- The latest Intel Atom® technology



### Powerful

- Equipped with the latest Intel Atom® series x7-E3950 (Apollo Lake)



### Sunlight readable

- Optimum readability in difficult visibility conditions
- Reliable functionality even outdoors



### Touch screen

- Select between resistive and capacitive touch screen
- Both touch screen variants can be operated with gloves
- Extremely break- (IK08) and abrasion-resistant front sides



### Robustness

- IP66 certified
- Vibration and impact resistance acc. to class 5M3
- Wide operating temperature range from -30°C to +60°C
- Sturdy aluminium die-cast case
- Resistant to a wide range of chemicals and UV radiation as well as adverse weather conditions
- Screwless design for simplified cleaning



### Power supply

- Wide-range power adapter for flexibly connecting a 12 V – 48 VDCIN power supply
- Input voltage range 9 – 60 VDCIN



### Sensors & data security

- Automatic brightness adjustment
- Integrated proximity and acceleration sensor
- User identification via RFID
- Smartcard-secured VPN tunnel and integration in the ADS-TEC IoT service platform Big-LinX®



### Wireless – WLAN, Bluetooth, WWAN and GPS

- The latest WLAN standards for optimum roaming behaviour
- External antenna can be connected in the case of difficult transmission and reception conditions
- WWAN and GPS for outdoor applications
- Bluetooth for connecting scanners, etc.



### UPS

- UPS function allows to work without interruption, even if the forklift battery needs to be replaced
- UPS integrated in the interface cover, making it easy to replace
- Provides power for approx. 10 – 15 minutes of operation



### Ignition function on vehicles

- Terminal is switched on by means of ignition voltage
- The system is either disabled or shut down when the ignition key is removed

# VMT9000 Series Technical Data

		VMT9010	VMT9012	VMT9112	VMT9015
<b>Housing</b>		Fanless die-casting aluminium housing powder-coated			
<b>Touch screen</b>		Break- and abrasion-resistant front sides			
		Resistive industrial touch screen	-	-	Resistive industrial touch screen
		PCAP multi-touch			
<b>Display</b>	LED backlight	10" TFT	12.1" TFT	12.1" TFT (widescreen)	15" TFT
	Resolution	XGA 1024 x 768 pixels	XGA 1024 x 768 pixels	WXGA 1280 x 800 pixels	XGA 1024 x 768 pixels
	Colours	max. 16.2 million	max. 16.2 million	max. 16.2 million	max. 16.2 million
		All displays are sunlight readable			
<b>Front keys</b>		Four freely configurable front keys			
<b>System versions</b>		Intel Atom® x7-E3950 2.0 GHz + 4GB LPDDR4 RAM Intel Atom® x7-E3950 2.0 GHz + 8GB LPDDR4 RAM			
<b>On-board mass storage</b>		64 GB eMMC			
<b>Mass storage</b>		Optional: 128 GB SSD			
<b>Interfaces</b>	USB	1 x USB 3.0 in side cover 3 x USB 3.0			
	Serial	COM1 (RS232, 5-V supply can be switched in) Optional: COM2 (RS232)			
	CAN	Optional			
<b>Network</b>		2 x 1 Gbit/s Ethernet RJ45			
<b>Wireless</b>	WLAN	Optional: IEEE 802.11a/b/g/n/ac, incl. connection for external antenna			
	WWAN	Optional: GPRS, EDGE, HSPA+, LTE			
	WPAN	Optional: Bluetooth V4.1, V4.0 LE, V3.0+HS, V2.1+DER			
<b>Position monitoring</b>		Optional: GPS through the connection of an external antenna			
<b>Sound</b>		Integrated speaker			
<b>RFID</b>	Supported transponders	Optional: LEGIC advant ATC, LEGIC card-in-card solution AFS, LEGIC prime MIM, NXP MIFARE DESFire, NXP MIFARE plus, NXP MIFARE Smart MX, Texas Instruments Tag-It, EM Microelectronics EM4035, Infineon my-d, NFC Forum Tag types 2/3/4, NXP Ultralight, NXP MIFARE Classic (UID), Sony Felica (plain text), Inside Contactless (UID), HID iClass (UID)			
		Brightness sensor, proximity sensor, acceleration sensor			
<b>Sensors</b>		Brightness sensor, proximity sensor, acceleration sensor			
<b>Power adapter (internal)</b>		Rated voltage 12-48 VDCIN (tolerance: 9-60 VDCIN) Ignition function via vehicle ignition Optional: uninterruptible power supply (UPS), typically 10 – 15 min			
<b>Operating system</b>		Windows® 10 IoT Enterprise, Linux, IGEL Linux			
<b>Weight</b>		approx. 3.2 kg	approx. 3.65 kg	approx. 3.7 kg	approx. 4.7 kg
<b>Environment</b>	IP protection	IP66 all-round protection			
	Impact-resistant front	IK08 acc. to EN 62262			
	Operating temperature	-30 °C to +60 °C			
	Storage temperature	-40 °C to +85 °C			
	Humidity	95% non-condensing			
Vibration and impact		Class 5M3 acc. to EN 60721-3-5			
<b>Accessories</b>	Brackets	Optional: various mounting adapters and RAM mounting solutions			
	Power adapter	Optional: table power adapter 230 VAC at 24 VDC			
	Connection cable	Optional: cable kit for connection to forklifts			
	Antenna	Optional: external WLAN antenna with magnetic base			
<b>Dimensions (W x H x D)</b>		277 x 249 x 50 mm	312 x 277 x 50 mm	331 x 256 x 50 mm	380 x 326 x 50 mm



An overview of all accessories and the technical dimensional drawings can be found at:  
[www.ads-tec.de/en/industrial-it/terminals/vmt9000-series/download.html](http://www.ads-tec.de/en/industrial-it/terminals/vmt9000-series/download.html)

# Security through software tools and ADS-TEC service

## Focus is on the customer **Services and individual configuration**

ADS-TEC continues to support you after you purchase a device and offers various service agreement options. Furthermore, the VMT9000 series with Big-LinX – the IoT service platform from ADS-TEC – is prepared for Industry 4.0 applications in logistics.

	without service package	BASIC ads-tec Service	SILVER ads-tec Service	GOLD ads-tec Service	FCC ads-tec Service
Protection against technical malfunctions	– *	✓	✓	✓	–
Contract term	– *	36/60 months	36/60 months	36/60 months	–
Processing time of the industrial IT product in the event of service	20 AT	10 AT	5 AT	3 AT	–
Protection against mechanical damages	– *	–	–	–	–
Assumption of repair costs also for mechanical damages	– *	–	–	–	✓

### ADS-TEC Services **The packages at a glance**

In order to cover technical malfunctions it is possible, beyond the statutory warranty, to purchase an ADS-TEC industrial IT product for an extended service. In this way, it is possible to have longer-term protection against repair costs due to technical malfunctions.



### Secure connection in the event that service should be necessary **With the ADS-TEC Big-LinX® remote management client**

With the Windows-based client, always stay securely connected to ensure smooth operation of the vehicle mounted terminals.

- Secure connection by means of Smartcard-secured VPN tunnel
- The software, firmware and BIOS are kept up-to-date at all times via the connection to the ADS-TEC IoT service platform Big-LinX

With Big-LinX, a central platform for remote maintenance of any number of terminals is available for technicians or service groups.

\*only contractually agreed warranty



Company headquarters (above) in Nürtingen near Stuttgart, production site in Wilsdruff near Dresden

**The ADS-TEC Group Technology for Professionals**

For decades, we follow the latest technologies for the best benefit of our customers. Depth of development and process „Made in Germany“ distinguish us, so that we remain able of acting over long periods of time. On this basis we are a strong and reliable partner in the fields of “Industrial IT” and “Energy”.

**Added values For the success of our customers**

- Our products have been developed in-house for over 35 years
- 100% depth of development is the basis for long-term and individual solutions
- Customised solutions based on tried-and-tested standard products
- Partnerships with market leaders in industry and the energy sector
- Cloud-based IoT solution kit for Industry 4.0 applications and management of our battery storage systems
- Highest safety standards for worldwide data communication
- In-house laboratory and testing facilities for maximum battery safety
- Extensive range of service offerings
- Permanent technology transfer in cooperation with universities
- Involvement in networks and associations as well as research projects funded by federal and state governments



ads-tec GmbH  
 Heinrich-Hertz-Straße 1  
 72622 Nürtingen  
 Phone +49 70 22 25 22-200  
 Fax +49 70 22 25 22-402  
 sales@ads-tec.de  
 www.ads-tec.de

